



Green Glue Compound

SOUND INSULATION MATERIAL



Green Glue Compound is a unique damping product that is ideal for new construction and renovation projects. It is the most popular and cost-effective soundproofing material on the market.

PROPERTIES

The compound's unique properties act as a damping material to dissipate the vibrations caused by sound waves as they travel through ceilings, walls and floors.

Independent lab tests prove that using Green Glue Noiseproofing Compound dissipates up to 90 percent of noise. Unlike other soundproofing products, Green Glue Noiseproofing Compound is ideal for dissipating low frequency noise common with home entertainment and theater systems.

It takes just a few minutes to apply Green Glue Noiseproofing Compound to an average piece of drywall (or other rigid construction material). It's easy to soundproof a room in one day, or less. For best results, cure time is seven days, and the Compound reaches its peak performance 30 days after application.

Green Glue Noiseproofing Compound has been proven to work in conjunction with the following materials:

DRYWALL - Click [here](#) for recommendations on drywall assemblies. You may use factory-damped drywall, but you can save yourself the extra expense by simply using extra layers of standard drywall with Green Glue Noiseproofing Compound.

WOOD PRODUCTS - Medium-density fiberboard (MDF), Oriented strand board (OSB) and plywood for applications like floors, soffits, seating risers in home theaters, stages, loudspeaker cabinets, and others.

INSULATION - common building fiberglass (yes, the fluffy pink stuff) works just as well or even better than pricier insulation materials.

Dryadon 40, Galatsi – Athens, ZC. 111 46

T:+30210 – 22.20.601, F: +30210 - 22.22.691

Web Site: <http://www.noisecontrol.gr>, email: info@noisecontrol.gr



SOUNDBOARD - we recommend using as an underlayment for flooring rather than for walls and ceilings because soundboard lacks the mass required for effective damping.

MASS LOADED VINYL - MLV and other limp mass products with Green Glue Noiseproofing Compound.

SHREDDED RUBBER UNDERLAYMENTS - the heavier and thicker, the better. Use compound on a solid surface and not on mesh or open-web underlayments.

STEEL STUD WALLS - Green Glue Noiseproofing Compound also performs outstandingly with steel stud walls.

Please ask for detailed information about specific wall types and materials.

PACKAGING - CONSUMPTION

- **Green Glue Compound (cartridge):** Cartridge 0,828lt – one cartridge for 1,5sqm (mean consumption).
- **Green Glue Compound (pail):** Pail 18,9lt – one pail for 34sqm (mean consumption).